







WORLD INTELLEC UAL PROPERTY ORGANIZATION International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: H02K 3/00

A2

(11) International Publication Number:

WO 99/29013

· | 4

(43) International Publication Date:

10 June 1999 (10.06.99)

(21) International Application Number:

PCT/EP98/07738

(22) International Filing Date:

30 November 1998 (30.11.98)

(30) Priority Data:

9725316.5

28 November 1997 (28.11.97) GB

(71) Applicant (for all designated States except US): ASEA BROWN BOVERI AB [SE/SE]; S-721 78 Västerås (SE).

(72) Inventor; and


(75) Inventor/Applicant (for US only): LEIJON, Mats [SE/SE]; Hyvlargatan 5, S-723 35 Västerås (SE).

(74) Agent: NEWBY, Martin, John; J.Y. & G.W. Johnson, Kingsbourne House, 229–231 High Holborn, London WC1V 7DP (GB). (81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

Without international search report and to be republished upon receipt of that report.

(54) Title: HIGH VOLTAGE ROTATING ELECTRIC MACHINES



(57) Abstract

A rotating electric machine for direct connection to all types of high-voltage networks, in which the magnetic circuit adapted for high voltage comprises a rotor (7), stator (6) and at least one winding. The winding, or at least one of the windings, comprises cooled conductor means (3), preferably cooled superconducting means, surrounded by a solid insulation system (4).